

Einführung

Das CLI steht erst ab Squeeze 2.5 zur Verfügung.

Im Projektverzeichnis von Squeeze (htdocs unter Windows, /var/www/html/squeeze unter Linux) liegt das CLI (Kommandozeilen-Tool) für Squeeze namens **squeezer**.

Mit diesem Tool sind administrative Tätigkeiten möglich, die ggf. nicht über die HTTP Schnittstelle oder Benutzeroberfläche möglich sind. Zusätzlich lässt sich die Verwendung des CLIs mittels Skripten automatisieren, falls gewünscht.

```
www-data@1d744d78f4c3:~/html/squeeze$ ./squeezer
Xdebug: [Step Debug] Could not connect to debugging client. Tried: 172.17.0.1:9003 (through xdebug.client_host/xdebug.client_port) :-(

Squeezier

Usage:
  command [options] [arguments]

Options:
  -h, --help           Display help for the given command. When no command is given display help for the list command
  -q, --quiet          Do not output any message
  -V, --version         Display this application version
  --ansi|--no-ansi     Force (or disable --no-ansi) ANSI output
  -n, --no-interaction Do not ask any interactive question
  -v|vv|vvv, --verbose Increase the verbosity of messages: 1 for normal output, 2 for more verbose output and 3 for debug

Available commands:
  completion           Dump the shell completion script
  help                 Display help for a command
  list                List commands
  ci
  ci:strict-types
  jobs
  jobs:schedule        Schedules internal jobs for tenants
  server
  server:check         Checks the System functionality
  server:migrate       You can use this command to migrate more then one tenant or directly all tenants on server
  server:reindex        Reindex all documents of all tenants.
  setup
  setup:server         Configure and setup a squeeze server using yaml settings given via either stdin or config option.
  setup:tenant         Configure and setup a squeeze tenant using yaml settings given via either stdin or config option. You can also pass a tenant argument
  tenant
  tenant:backup        Backup a tenant
  tenant:check         Checks the tenant functionality
  tenant:reindex        Reindex documents of all document classes
  tenant:restore        Restore a tenant from backup:tenant dump
  tenant:upload-file   Uploads a file into the processing pipeline for a specific tenant.
```

Verwendung

Windows

Öffnen Sie ein Terminal (Kommandozeile oder Powershell) und verwenden sie diese Befehle:

```
# htdocs Ordner öffnen, nutzen Sie hier Ihren Installationspfad  
cd C:\\SQUEEZE\\htdocs  
  
# CLI testen  
php ./squeezer --help
```

Linux

```
# Installationspfad öffnen  
cd /var/www/html/squeeze  
  
# CLI testen  
. ./squeezer --help
```

Befehle

Das Tool dokumentiert die Unterstützen Befehle und ihre Argumente selbstständig. Nutzen sie folgendes Flag, um herauszufinden welche Befehle es gibt und was sie tun:

```
# Mögliche Befehle auflisten  
. ./squeezer  
# oder  
. ./squeezer list  
  
# Ausgabe:  
Squeezers  
  
Usage:  
command [ options ] [ arguments ]  
  
Options:  
-h, --help           Display help for the given command. When no command is given display  
help for the list command  
-q, --quiet          Do not output any message  
-V, --version         Display this application version
```

```
--ansi|--no-ansi Force (or disable --no-ansi) ANSI output
-n, --no-interaction Do not ask any interactive question
-v|vv|vvv, --verbose Increase the verbosity of messages: 1 for normal output, 2 for more
verbose output and 3 for debug
```

Available commands:

```
completion          Dump the shell completion script
help               Display help for a command
list               List commands
ci
ci:strict-types
jobs
jobs:schedule      Schedules internal jobs for tenants
server
server:check        Checks the System functionality
server:migrate     You can use this command to migrate more then one tenant or directly
all tenants on server
server:reindex      Reindex all documents of all tenants.
setup
setup:server       Configure and setup a squeeze server using yaml settings given via
either stdin or config option.
setup:tenant        Configure and setup a squeeze tenant using yaml settings given via
either stdin or config option. You can also pass a tenant argument to specify for which
tenant installation should be done
tenant
tenant:backup      Backup a tenant
tenant:check        Checks the tenant functionality
tenant:reindex     Reindex documents of all document classes
tenant:restore      Restore a tenant from backup: tenant dump
tenant:upload-file Uploads a file into the processing pipeline for a specific tenant.
```

So lassen Sie sich einen Befehl erklären:

```
# Hilfe für Command server:check ausgeben
./squeezr server:check --help

# Ausgabe:
Description:
Checks the System functionality
```

Usage:

```
server: check
```

Options:

-h, --help Display help for the given command. When no command is given display help for the list command

-q, --quiet Do not output any message

-V, --version Display this application version

--ansi| --no-ansi Force (or disable --no-ansi) ANSI output

-n, --no-interaction Do not ask any interactive question

-v| vv| vvv, --verbose Increase the verbosity of messages: 1 for normal output, 2 for more verbose output and 3 for debug

Revision #4

Created 23 June 2023 12:06:21 by Fabian Terstegen

Updated 17 August 2023 06:30:06 by Fabian Terstegen