

Otris SOAP

Vor der Übergabe eines Dokumentes an die Otris SOAP Schnittstelle ist es möglich Modifikationen am Dokument aber auch an den Verbindungsparametern vorzunehmen. Hier ein Beispiel für einen solchen UserExit:

```
<?php
```

```
use Squeeze\xDoc;
```

```
use Squeeze\xReturnObject;
```

```
// vor Squeeze 2.5: BeforeExport0trisSoap anstatt Before0trisSoapExport
```

```
function BeforeExport0trisSoap(xDoc $doc, array $soapDoc): xReturnObject
```

```
{
```

```
    try {
```

```
        $company = $doc->getFieldByName(' Company' );
```

```
        if ($company === null) {
```

```
            // return an error if the Squeeze field does not exist
```

```
            return new xReturnObject(false, 500, 'Field Company does not exist', $soapDoc);
```

```
        }
```

```
        // If the value of the field Company is equal 1000
```

```
        if ($company->getValue()->value == '1000') {
```

```
            // use a different server
```

```
            $soapDoc['parameter']['ServerUrl'] = 'http://123.123.123.123:11001';
```

```
        }
```

```
        // return a new result with the modified $soapDoc variable
```

```
        return new xReturnObject(true, 200, 'UserExit BeforeExport0trisSoap successful',  
$soapDoc);
```

```
    } catch (Exception $e) {
```

```
        // in case of an exception return an error
```

```
        return new xReturnObject(false, 500, $e->getMessage(), $soapDoc);
```

```
    }
```

```
}
```

Revision #2

Created 29 September 2020 04:04:57 by Phillip Langer

Updated 1 August 2023 13:16:39 by Ulrich Eckhardt